

Protection spirals

ACCESSORIES

TECHNICAL FEATURES

Technical features:

- The spiral is made of high-density polyethylene that is practical, quick and simple to fit.
- Suitable for the protection or containment of one or more hoses.
- The raw material used has good resistance to abrasion and UV rays.

Working temperature:

- from -50°C to +100°C
- from -58°F to +212°F



Article Code	Internal Diameter (mm)	Outside Diameter (mm)	Wall Thickness (mm)	Strip Width (mm)	Weight (g/m)	Hose Diameter Range (mm)	Length (m)
GS0907	7	9	1.0	6.5	22	8÷10	150
GS128	9.5	12	1.7	10	46	10÷17	50
GS1612	12.5	16	1.8	12	76	13÷22	50
GS2016	16	20	1.8	14.5	86	16÷27	50
GS2520	21	25	2	21	112	21÷35	50
GS3227	27	32	2	24	177	27÷44	50
GS4036	34	40	2.5	30	217	34÷55	50
GS5044	44	50	3	35	278	44÷70	50
GS6356	55	63	3.5	40	588	55÷87	20

GS7567	66	75	3.4	40	813	67÷103	20
GS9080	79	90	5	45	1033	80÷122	20
GS110100	99	110	5.5	55	1200	100÷152	12
GS125114	114	125	5.6	55	1638	115÷174	12
GS140129	129	140	5.6	55	1807	130÷196	8
GS160148	148	160	6	60	2031	150÷224	6

For any further information about the optional items, please contact the sales office ()